## DiECi



## SAMSON

*75.10* 



di€ci.com

## PERFORMANCE Vehicle model SAMSON 75.10 Maximum capacity 7500 kg (16535 lb) Maximum lifting height 9,65 m (31,7 ft) Maximum horizontal extension 5,40 m (17,7 ft) Fork swiveling angle 134° Pull-out force 5700 daN (12814 lbf) Towing force 7300 daN (16411 lbf) Maximum climb angle 40% 12100 kg (26676 lb) Unladen weight Max speed (referred to wheels with maximum permitted diameter) 30 km/h (18,6 mph) Vehicle model **SAMSON 75.10** Lifting 15,1 s Descent 9.9 s Extension 10,4 s Retraction 4.1 s Forward swiveling 4,6 s Reverse swiveling 2,0 s Vehicle model SAMSON 75.10 Brand Nominal power 93 kW (125 HP) @rpm 2200 rpm Operation 4-stroke Mechanical direct Injection Number and arrangement of cylinders 4, Vertical in line Displacement 4485 cm<sup>3</sup> (274 in<sup>3</sup>) Consumption 230 g/kWh (378,35 lb/Hp h) @rpm 2200 rpm Stage IIIA/Tier 3 **Emission standard** Cooling system Liquid Intake Turbo compressor after-cooler **DIFFERENTIAL AXLES** Vehicle model **SAMSON 75.10** Type of axles 2 steering, with 4 planetary reduction gears Type of steering 4 wheels / transversal / 2 wheels Front axle Rigid (at Leveling request) Rear axle Swinging Service braking Oil bath with servo brake on front and rear axle with double hydraulic system Negative actuation with electrical control Parking braking **HYDRAULIC SYSTEM SAMSON 75.10** Vehicle model Hydraulic pump type Gear pump for power steering and movements Hydraulic pump capacity 130 L/min (34,3 gal/min) Max. operating pressure 26,0 MPa (3771 psi) Distributor control 4in1 proportional Joystick REFUELING SAMSON 75.10 Vehicle model Hydraulic system (total) 160,0 L (42,27 gal) Fuel tank 105,0 L (27,74 gal) Vehicle model **SAMSON 75.10** Transmission type Hydrostatic with variable flow pump Hydraulic motor Hydrostatic with continuous automatic adjustment

Electrohydraulic

**SAMSON 75.10** 

18x22.5"

Servocontrolled 2-speed

With inching pedal for controlled forward movement

Reversal

Inching

Transmission gearbox

Vehicle model Standard tires

C. 11 (2011)	
DIMENSIONS	
Vehicle model	SAMSON 75.10
A	440 mm (17,3 in)
В	1480 mm (58,3 in)
C	2950 mm (116,1 in)
D	1330 mm (52,4 in)
F	4820 mm (189,8 in)
G	5910 mm (232,7 in)
Н	2490 mm (98 in)
I	940 mm (37 in)
L	1920 mm (75,6 in)
M	2380 mm (93,7 in)
0	4730 mm (186,2 in)
P	1700 mm (66,9 in)
Q	4400 mm (173,2 in)
T	100 mm (3,9 in)







